

## PB Series 4600 / 2200 Pro



Ivory white



Cable management design allows easy routing of cables for aesthetics and safety measures.

### Features

- Capable of controlling 2 cash drawers
- 1 PCI extension slot for option installed
- One LAN port Ethernet 10/100/1000 Base T with LAN status indicators on jack
- Equip with 6 USB connectors
- Support 4 serial ports for numerous applications.
- Compatible with windows XP, WEPOS, POSReady, Win 7 and Linux operating environments
- Screw-free architecture for easy maintenance access
- Spill proof design
- Concealing design allows easy routing of cables and help to conceal dangerous and unsightly cables



Specification	PB-4600	PB-2200 pro
Processor	Intel 575 CPU (2.0GHz - 1MB Cache, 667MHz FSB) or Intel T3100 Dual Core CPU (1.9GHz - 1MB Cache, 800MHz FSB) Core 2 Duo P8400 CPU (2.26GHz - 3MB, 1066MHz FSB) Core 2 Duo T9400 CPU (2.53GHz - 6MB Cache, 1066MHz FSB)	VIA C7 1.5GHz
System Memory	Default 1 GB DIMM socket x 2 ,DDR-2 667/800MHz ,Max 4GB	Default 512MB Expandable to 2GB DDR2 400/533 memory
Video Memory	Support DVMT 5.0	16MB-64MB, shared with system memory
Power Supply	+12V DC power adaptor, 80W	
Speakers	Built-in	
OS support	WEPOS, Linux, XP pro, POSReady, Win 7	WEPOS, Linux, XP pro, POSReady, Win CE
Compliance	FCC, CE (class A), RoHS	
Expansion		
Storage Device	2.5" SATA HDD or optional SSD	80 GB or above
Connectivity		
Stereo audio line out / mic in	YES	
CF card slot (Type II, memory card only)	N/A	Optional
LAN Port	10/100/1000 Mb	10/100 Mb
Parallel Port	x 1	
Serial Port	4, DB9 X 4	
UPS Port	N/A	x 1
Standard USB Port	6 ports on the I/O plate	
Proprietary USB Port	1 for side mount option	
VGA Port	D-Sub 15 pin	
CR Port	Yes, one port control 2 CRs	
PS/2 KB & MOUSE	YES	
Color options	Black / Ivory white	
Physical Dimension		
Dimension (W x D x H in mm)	279 mm (W) x 243 mm (D) x 114 mm (H) (11.0" x 9.6" x 4.5")	
Weight (N. W. in kg)	4	
Environment		
Operation Condition	5°C~+40°C (41°F~+104°F), 20%RH~80%RH, non-condensing max. wet bulb 26°C (78.8°F)	
Storage Condition	-20°C~60°C (-4°F~140°F) , 10%RH~80%RH, non-condensing max. wet bulb 28.9°C (84.0°F)	
Options		
24V Powered Port (24V powered)	x 1, Option (Power adaptor must upgrade to 120W)	N/A
2 <sup>nd</sup> HDD	N/A	Yes
LM-7112 / TM-7112	12.1" TFT active matrix LCD panel (TM-7112 is touch panel)	
LM-2108	8" TFT LCD, 800x600 resolution	
Im-2110	10.4" TFT LCD, 800x600 resolution	
KP-210	Side mount programmable keypad with optional MSR and Smart card reader (Upgrade kit with LM-7112 / TM-7112 )	
BC-300	Bar Code card reader, USB interface (Upgrade kit with LM-7112 / TM-7112 )	
PD-2601	2 x 20 VFD customer display, 5 x 7 dots matrix RS232 interface default (USB interface optional)	2 x 20 VFD customer display, 5 x 7 dots matrix USB interface default(RS232 interface optional)
PD-307U	2 x 20 LCD customer display, USB interface	
Wireless LAN	802.11 a/b/g/n with USB interface	
SSD	S-ATA I (150MB/s,minimum 8G)	N/A
COM-5 / 6	COM-5 & COM-6	
RAID Card	RAID-1	N/A

❖ The product information and specifications are subject to change without prior notice.

2010 V.01

## Posiflex Technology (India) Pvt Ltd.

#985, 1st A Main Road, 4th Cross, New Thippasandra,  
Bangalore 560 075. India  
Ph : + 91 80 415 23 515 Fax:+91 80 415 36 089  
Email: sales@posiflexindia.com  
www.posiflexindia.com

