



Customer Pole Display

PD-7600 Series



- Graphic STN LCD (liquid crystal display) in blue background with white backlight.
- Stand alone Pole Display for POS application.
- Four-line display with 30 Arabic letters or 15 Chinese characters per line
- 240 by 64 dots for graphic display.
- Adequately sized characters for easy viewing (8.47 mm by 4.24 mm per digit).
- Long life and trouble free operation.
- Display contrast adjust buttons on front surface
- 15°, 30° and 45° adjustable viewing angles.
- Display frame can rotate horizontally 270° freely.
- Supports ESC/POS commands.
- Simple installation.
- Serial (RS232) interface.
- Case color choices: ivory, black.

MODELS, LANGUAGES & CODE TABLES

PD-7610: Simplified Chinese, GB-2312

PD-7620: Traditional Chinese, BIG-5

PD-7630: Arabic, Windows code page 01256 (with Arabic numerals addressed in <80> ~ <89> of code page 1)

PD-7200 Series



- Ergonomic designed.
- Stand-alone LCD pole display.
- Power and data on same connector when applied with Posiflex POS Terminal.
- Wide operating temperature range (0°C to 50°C).
- LCD viewing angle: 60 degrees vertically, 50 degrees horizontally.
- 3 User defined characters (16x16 dot).
- Character size 18.35x17.87 mm for 16x16 format.
- Character size 18.35x8.91 mm for 8x16 format.
- US-ASCII character (8x16 or 6x8 dot).
- Chinese GB or BIG-5 character (16x16 dot).
- RS-232C interface.
- Software self test.
- Command emulation modes include Epson, Noritake and IEE (for Chinese only).
- Display head 330° rotatable.
- Display head tilt angle 14.5°/ 30°.
- A rock switch on base for power ON/OFF if using AC power adaptor.

PD-2600 Series



- Bright VFD (vacuum fluorescent display) with green or blue filter
- Stand along pole display.
- Two-line display with 20 characters per line.
- Adequately large characters for easy viewing (9.03 mm by 5.25mm).
- Long life and trouble free operation.
- 15°, 30° and 45° adjustable viewing angles.
- Total height 410 mm.
- Display frame can rotate horizontally 270° freely.
- Various command emulation modes selectable by DIP switch.
- Support 12 Code Pages of 128 characters each.
- Support 12 international character sets of 12 characters each.
- Simple installation.
- Selectable between Serial (RS232) interface model and USB interface model.
- Supports UPOS 1.8 and is WEPOS ready.

PD-2500 Series



- Stand-alone Pole Display with a mount plate and small base size with a rock power ON/OFF switch on base.
- Euro dollar sign supported in code page 858.
- Various command emulation modes selectable by DIP switch.
- Total height 556 mm above mounting plate with a strong, stable pole.
- 0° to 45° tilt in four steps and 300° swivel for best viewing effect.
- Cabinet color choices: Ivory white, Black.

PD-2300



- Bright green fluorescent display.
- Two-line display with 20 characters per line.
- Adequately large characters for easy viewing (9.03 mm by 5.25 mm).
- Long life and trouble free operation.
- Generous base best for freely stand alone.
- Two adjustable viewing angles.
- Pole height adjustable.
- Display frame can slide horizontally and rotate 360° freely.
- Brightness adjustable by software.
- Simple installation.
- Pole high adjustable.
- Selectable interface of Serial interface with pass through capability and USB interface.
- Multiple choices for power supply source.
- Support Euro dollar sign.

Multifunctional POS Peripherals

Customer Pole Display



PD-2100/2200 Series



- Bright vacuum fluorescent display.
- Two-line display with 20 characters per line.
- Large characters for easy viewing (11.25mm by 7.2 mm).
- Long life and trouble free operation.
- Secure construction with bumper best for screw on operation in PD-2100 Series. Generous base best for freely stand alone application in PD-2200 Series.
- Two adjustable viewing angles.
- Pole height adjustable.
- Display frame is horizontally slidable, and 360° rotatable freely.
- Brightness adjustable by software.
- Simple installation.
- Direct interface connection with computers and peripherals.
- Standard Serial interface for both series and with pass through capability for PD-2200 Series.
- Multiple choices for power supply source.
- Support Euro dollar sign.

PD-300 Series



- Two - line LCD display with 20 characters per line.
- Dark blue character with yellow green back-light.
- Easy viewing characters (6.0 mm by 9.66 mm).
- Display area 143 mm by 21 mm.
- Euro dollar sign supported in USA/European font table.
- Selectable command emulation modes including PST and EPSON command emulation modes.
- Long life, trouble free and user friendly operation.
- Composed of several members in the family for versatile applications as tabulated below.



Posiflex Technologies, Inc.

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan, R.O.C.
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

