

POSIFLEX



FORTIS

FORTIS XP Series

Posiflex now present a whole new generation POS terminal, which is a combination of touch screen, printer, MSR, and the most reliable FanFree structure. This integrated solution of XP-2000 series not only uncomplicated, but also carrying a brilliant performance to user in order to face the busiest situation.



www.posiflex.com

FORTIS XP SERIES



XP-2007



XP-2008H



XP-2010H



XP-2012H



Integrated MSR



Clear LED indicator panel



Integration of Customer Pole Display



Integration of 2nd Display

- All-in-one integrated system including touch screen, thermal printer and MSR.
- The most reliable Fanfree structure for harsh environment.
- Thermal printer with paper jams easy to clean design.
- Support Win XP Pro, POSReady, WEPOS and Linux environment.
- High quality TFT active matrix LCD panel with High resolution.
- Vertical type LCD panel with easy tilt angle adjustment.
- Durable resistive type touch sensor for broad range of application.
- Supports SSD (Solid-State Drive) Data Storage Device.

ITEM	XP-2007	XP-2008H	XP-2010H	XP-2012H
CPU	Intel Celeron M 600Mhz , 512K Cache			
Chipset	Intel 910MLE + ICH6-M			
VGA port	D-SUB 15Pin			
LCD Display	Digital 7" TFT LCD Panel 800x600 resolution	Digital 8" TFT LCD Panel 800x600 resolution	Digital 10.4" TFT LCD Panel 800x600 resolution	Digital 12.1" TFT LCD Panel 1024x768 resolution
DRAM memory	SO-DIMM X 1, DDR-II, 512MB upgradable to 1GB			SO-DIMM X 1, DDR-II, 1GB
Serial port	1, DB9 X 1 on the I/O Plate			
CR port	X1			
Standard USB port	4 port on the I/O plate			
Audio port	buzzer only			
Ethernet port	10/100 Mb			
Touch function	N/A	USB Interface		
Touch sensor	N/A	5 Wire Touch Pad		
Storage device	DOM , 1GB			
Power switch	On the top side			
Mechanical installation	ECR look like			
Power saving	Suspension mode			
Power supply	power adaptor, 60W			
Indicator LED and control panel switch	Power ON/ standby, bi-color LED, Printer Error (RED), Paper Out (RED), paper feed and power ON switch			
Fanless system	Yes			
OS support	Linux , Window CE. WEPOS. POSReady			
Printer build in	2" thermal printer (60mm/sec)			
Printer auto cutter	Option (Upgradable auto cutter)		Yes	
Paper width	58mm			
Maximum printable width	48mm max.			
LCD panel tilt angle (degree)	14~55			
Dimension (W x D x H / mm)	325 x 386.2 x 249.6 mm		325 x 386.2 x 298.1 mm	325 x 386.2 x 331.2 mm
Weight (N. W. in kg)	3.87 kg	4.15 kg	5.75 kg	6.54 kg
Option peripheral				
MSR	2 or 3 tracks & JIS-II			
Keyboard	84 keys mini KB with USB Interface			
Customer pole display	PD-2606: 2x20 VFD display / PD-330: 2x20 LCD Display / PD-7630: LCD Display			
SSD HDD	SATA SSD (8GB Minium)			
2.5" SATA HDD	2.5" SATA HDD (80GB Minium)			
	Support XP Professional on upgrade to SSD HDD or 2.5" SATA HDD storage device			
2nd Display	LM-2208: 8" TFT LCD ,800x600 resolution, LED Backlight			LM-2212: 12" TFT LCD, 1024x768 resolution, LED Backlight TM-2212: 12" TFT LCD, 1024x768 resolution, LED Backlight, Support touch panel
MSR for 2nd Display	N/A			SD-300, Finger Printer & MSR (2 or 3 tracks & JIS-II)

The product information and specifications are subject to change without prior notice.

2009 V.1