


Make Your Business Look More Attractive

Fanless POS Terminal

The RT-5000 Series radiates in its new Design - Featuring an ultra-slim and sleek look that exhibits elegance. it is uncompromising to the space requirements and provides better cable management and easy maintenance.

Model No.

RT-5015 5016



INTEL -I3 / I5
Processor



15" True-flat
PCAP Touch



3
YEAR
WARRANTY



4GB RAM-
64GB / 128GB
SSD

Ph : 9849032655

www.primebarcodesolutions.com

RT-5015/5016

Specification	RT-5015	RT-5016
Processor	Intel Skylake Core i3-6100U Dual Core CPU, 2.30 GHz, 3M Cache	
System Memory	DDR4 SO-DIMM slot x 2, max. 16GB	
Storage Device	SATA storage x 2	
Power Supply	12V/80W	
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request	

Display & Touch

LCD	15" TFT LCD	15.6" TFT LCD
Resolution	1024 x 768	1920 x 1080
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)	

I/O & Expansion

Serial Port	3, DB9 x 1 + RJ45 x 2, 5V/12V support on all COM ports	
Standard USB Port	4, USB 3.0 x 2 + USB 2.0 x 2; optional USB extension module to bring total USB port to 7 (USB 3.0 x 1 will no longer be available with the USB extension module)	
PoweredUSB Port	Optional PoweredUSB module with 24V + 12V (USB 3.0 x 1 will no longer be available with the PoweredUSB module)	
LAN Port	10/100/1000 Mb x 1	
Display Port	VGA via proprietary connector (12V support for Posiflex monitors) x 1 + mini DP x 1	
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer	
Audio	Internal 2W speaker x 1	
Expansion Slot	M.2 slot x 1	

Physical Dimension

Dimension (W x D x H in mm)	368 x 207 x 325	402 x 207 x 297
Weight (N. W. in kg)	5.4	5

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	

Built-in Options

WiFi	M.2 WiFi/BT module	
Camera	2MP	
AG Glass	Cannot co-exist with built-in camera	

Attachment Options

POS Monitor	9.7"/10.1" TFT LCD display (touch/non-touch)	
-------------	--	--